



## T.C. 3 Fume Control

### DESCRIPTION

T.C. 3 is a revolutionary fume suppressant for hydrochloric and sulfuric acids that performs with the aid of a foam blanket. T.C. 3 reduces the hydrogen gas produced in solution. Gas that is not produced cannot escape into the air. Hydrogen Chloride gas has been reduced to as little as 5 ppm in batch pickling operations where HCL is 15% w/v and temperatures are 140° to 150°F.

T.C. 3 is added at a ratio of 1/2% to 1% based on the volume of concentrated acid (1/2 to 1 gallon for each 100 gallons of acid). It can be added directly to the raw hydrochloric storage tanks.

### TYPICAL PROPERTIES

Form	Liquid
Weight	9 lbs/gal
Flash point	Over 200°F
Freezing point	10°F
Solubility in acid	Complete
Freeze-thaw recovery	Complete

### FOAMING COMPOUNDS

#### T.C. 20

This powder produces a detergent-type foam blanket on the surface of the pickling bath. No carryover to rinse bath. Use approximately 1/4 per 1000 gallons of bath solution.

#### T.C. 30

A new, inexpensive liquid foamer. A water clear, neutral solution that produces a detergent-type foam. Effective in both Sulfuric and Hydrochloric acid baths. Use approximately 1 pint per 1000 gallons of pickling solution.

#### T.C. 40

A liquid for use in Nitric-Hydrofluoric acids.

### ANTI-FOAM

A new extremely anti-foam emulsion for preventing or controlling foam in pickling baths, rinse tubs, or lime tanks. 10 to 50 parts anti-foam per million parts of foamer is suggested. Approximately 8 ounces per 1000 gallons of bath solution.